

Svasatori a tre taglienti - A 90°

NORMEX®

HSS	DIN		
TiAlN	335-C		

Per acciaio, ghisa, metalli leggeri e leghe non ferrose
Il rivestimento al nitruro di titanio e alluminio aumenta la durezza della superficie e li rende adatti anche per lavorazioni a secco



HSS + TiAlN

Ø testa max.	mm	6,3	8,3	10	10,4	12,4	13,4	15	16,5	16,5	20,5	25	31
Codice	F 7792 ...	1063	1083	1010	1104	1124	1134	1015	1164	1165	1205	1025	1031
F 7792/1	Cad. €												
Ø min. di svasatura	mm	1,5	2	2,5	2,5	2,8	2,9	3,2	3,2	3,2	3,5	3,8	4,2
Gambo Ø	mm	5	6	6	6	8	8	10	8	10	10	10	12
Lunghezza totale	mm	45	50	50	50	56	56	60	60	60	63	67	71

HSS	DIN		
TiN	335-C		

F 7792/3 - NORMEX®**F 7792/4 -** 

Ø testa max.	mm	6,3	8	8,3	8	10,4	12,4	15	16,5	16,5	19	20,5	23	25	31
Codice	F 7792 ...	3063	—	3083	—	3104	3124	3015	3164	3165	3019	3205	3023	3025	3031
F 7792/3	Cad. €		—		—										
Codice	F 7792 ...	—	4008	—	4010	—	4124	4015	—	4165	—	4205	—	4025	4031
F 7792/4	Cad. €	—		—		—		—			—		—		
Ø min. di svasatura	mm	1,5	2	2	2,5	2,5	2,8	3,2	3,2	3,2	3,5	3,5	3,8	3,8	4,2
Gambo Ø	mm	5	6	6	6	6	8	10	8	10	10	10	10	10	12
Lunghezza totale	mm	45	50	50	50	50	56	60	60	60	63	63	67	67	71

NORMEX®

Testa in metallo duro

HM	DIN		
K 20	335-C		

Per acciai duri e abrasivi con resistenza superiore a 1000 N/mm² e ghisa grigia superiore a 240 HB



Ø testa max.	mm	6,3	8,3	10,4	12,4	16,5	20,5	25	31
Codice	F 7792 ...	7063	7083	7104	7124	7165	7205	7025	7031
F 7792/7	Cad. €								
Ø min. di svasatura	mm	1,5	2	2,5	2,8	3,2	3,5	3,8	4,2
Gambo Ø	mm	5	6	6	8	10	10	10	12
Lunghezza totale	mm	45	50	50	56	60	63	67	71

NORMEX®

HSS	DIN		
	335-D		

Per acciaio, ghisa, metalli leggeri e leghe non ferrose



Ø testa max.	mm	16,5	20,5	25	31	37	40	50	63	80
Codice	F 7793 ...	2165	2205	2025	2031	2037	2040	2050	2063	2080
F 7793/2	Cad. €									
Ø min. di svasatura	mm	3,2	3,5	3,8	4,2	4,8	10	14	16	22
Cono Morse		1	2	2	2	2	3	3	4	4
Lunghezza totale	mm	85	100	106	112	118	140	150	180	190

ABC TOOLS

HSS	DIN		
	335-C		

Per acciaio, ghisa, metalli leggeri e leghe non ferrose
Con impugnatura in resina termoplastica



Ø testa max.	mm	12,4	15	16,5	20,5	25
Codice	F 7793 ...	4125	4015	4165	4205	4025
F 7793/4	Cad. €					
Ø min. di svasatura	mm	2,8	3,2	3,2	3,5	3,8
Lunghezza totale	mm	130	135	135	135	145

ABC TOOLS

HSS	DIN		
	335-C		

Per acciaio, ghisa, metalli leggeri e leghe non ferrose
Con attacco esagonale $\frac{1}{4}$ " - DIN 3126 C 6,3 - Per avvitatori elettrici

Attacco $\frac{1}{4}$ " - C 6,3

Ø testa max.	mm	6,3	8,3	10,4	12,4	16,5	20,5
Codice	F 7793 ...	6063	6083	6104	6124	6165	6205
F 7793/6	Cad. €						
Ø min. di svasatura	mm	1,5	2	2,5	2,8	3,2	3,5
Lunghezza totale	mm	31	31	34	35	40	41